



Horizontal Mount
 Insulated Core
 Approval Compliance: EN60938-2
 Dielectric Strength: 2000 Vrms
 Custom Design offered

Weight(g) : 40

| Part Number | Inductance (mH) | DCR (mΩ) | I rms (A) | Dim A | Dim B | Dim C | Dim D | Dim E | Dim F |
|--------------|-----------------|----------|-----------|-------|-------|-------|-------|-------|-------|
| VTX-522-0601 | 11.5 | 100 | 4.0 | 41.5 | 37.0 | 20.5 | 20 | 35.0 | Φ 0.8 |
| VTX-522-0602 | 8.0 | 55 | 5.0 | 41.5 | 37.0 | 20.5 | 20 | 35.0 | Φ 0.8 |
| VTX-522-0603 | 6.0 | 35 | 6.0 | 41.5 | 37.0 | 20.5 | 20 | 35.0 | Φ 0.8 |
| VTX-522-0604 | 2.9 | 18 | 8.0 | 41.5 | 37.0 | 20.5 | 20 | 35.0 | Φ 1.0 |
| VTX-522-0605 | 1.1 | 10 | 10 | 41.5 | 37.0 | 20.5 | 20 | 35.0 | Φ 1.0 |
| | | | | | | | | | |



VIGORTRONIX
 16 De Havilland Way
 Windrush Park, Witney
 Oxon, OX29 0YG, UK
 Tel: +44 (0)1993 777570
 Fax: +44 (0)1993 777580
 www.vigortronix.com

DRAWING

VTX-522-06XX Series

| Issue | Date | Drawn | PCN No | Checked |
|-------|----------|-------|--------|---------|
| 1 | 12-03-08 | BGH | | |
| 2 | | | | |
| 3 | | | | |

DRAWING NUMBER

VTX-522-06XX